## LUBRICANTS AND FLUIDS

| Part                  | Variant                               | Specification  |
|-----------------------|---------------------------------------|--|
| Engine oil            | Petrol vehicles 2.0L                  | SAE 5W-30 engine oil meeting specification WSS-M2C913-C.   |
|                       | Diesel vehicles 2.2L<br>(with DPF)    | SAE 5W-30 engine oil meeting specification<br>WSS-M2C934-B. If unavailable 5W-30 engine<br>oils to ACEA C2 specification may be used.                              |
|                       | Diesel vehicles 2.2L<br>(without DPF) | SAE 5W-30 engine oil meeting specification<br>WSS-M2C913-C. If unavailable 5W-30 engine<br>oils to ACEA A5/B5 specification may be used.                           |
| Main gearbox oil      | Manual transmission                   | Land Rover recommends Castrol BOT 350 M3.  |
| Main gearbox oil      | Automatic transmission                | Land Rover recommends Nippon AW-1 ATF.   |
| Power Transfer unit   | All vehicles                          | Land Rover recommends Castrol BOT 118+.  |
| Haldex coupling       | All vehicles                          | Land Rover recommends STAT OIL SL01-301.   |
| Rear differential oil | All vehicles                          | Land Rover recommends Castrol EPX.   |
| Power steering fluid  | All vehicles                          | Land Rover recommends Pentosin CHF202.   |
| Brake fluid           | All vehicles                          | Use Land Rover brake fluid. If unavailable for<br>topping up, a Low Viscosity, DOT4 brake fluid<br>that meets the requirements of ISO 4925 class<br>6 may be used. |
| Screen wash           | All vehicles                          | Screen wash with frost protection.   |
| Screen cleaning paste | All vehicles                          | Land Rover screen cleaning paste DNJ500340.  |
| Coolant               | All vehicles                          | Land Rover recommends 1:1 mixture of Texaco XLC and water.   |